

PUV 6000 SERIES COLORANTS



CHARACTERISTICS AND PROPERTIES: pigment dispersions in unsaturated polyester resin (styrene free) and suitable wetting and dispersant agents, do not contain photoinitiators.

COMPATIBILITY : all UV curing systems such as polyether-, epoxy-, polyurethane-, and polyester-Acrylate.

APPLICATION FIELD : paints for wood and furniture finishes, industrial coatings and printing inks.

| FULL SHADE | REDUCED SHADE | CODE | DESCRIPTION | COLOR INDEX | Pigment Content (% weight) |
|------------|---------------|------|----------------------------|-------------|----------------------------|
| | | 6001 | WHITE | PW 6 | 65 |
| | | 6002 | YELLOW OXIDE | PY 42 | 45 |
| | | 6005 | ORGANIC YELLOW | PY 154 | 24 |
| | | 6006 | GREENISH YELLOW | PY 184 | 50 |
| | | 6007 | REDDISH YELLOW transparent | PY 83 | 18 |
| | | 6008 | ORGANIC ORANGE | PO 34 | 19 |
| | | 6011 | MAGENTA | PR 122 | 12 |
| | | 6012 | ORGANICO RED | PR 254 | 18 |
| | | 6013 | RED OXIDE | PR 101 | 60 |
| | | 6015 | RED VIOLET | PV 19 | 15 |
| | | 6016 | VIOLET | PV 23 | 10 |
| | | 6018 | PHTALO BLUE | PB 15:2 | 12 |
| | | 6019 | ULTRAMARINE BLUE | PB 29 | 50 |
| | | 6020 | PHTALO GREEN | PG 7 | 15 |
| | | 6023 | BLACK OXIDE | PBk 11 | 50 |
| | | 6024 | BLACK | PBk 7 | 20 |

Values are to be considered as nominal and should be treated as a guideline. We suggest to perform always a preliminary compatibility test. The producer reserves the right to modify at any time these parameters, without giving advance notice, in order to respect the tolerance of colorimetric standards.

The colours here represented are by way of example, in terms of colour strength and shade. Colours might differ from real product depending on the printer and video installed.

Colorificio Migliavacca 1919 Srl - Via dell'industria, 20 - 24126 BERGAMO (ITALY) – Tel +39 035.243.879
www.colorificiomigliavacca.it - E-mail: info@colorificiomigliavacca.it
 member of **AMERICAN COLORS INC. (USA)**